


NOTES:

1. PRECAST REINFORCED CONCRETE TOPS, RISERS, BASES AND REBARS SHALL CONFORM TO LATEST ASTM C-478 STD. SPECIFICATIONS.
2. INTERIOR AND EXTERIOR OF MANHOLE SHALL BE COATED IN ACCORDANCE WITH SECTION 02555 OF CITY OF SAVANNAH STD. SPECIFICATIONS.
3. MANUFACTURER CERTIFICATION THAT MANHOLE MEETS ASTM SPECIFICATION SHALL BE SUBMITTED TO CITY OF SAVANNAH.
4. FOR MANHOLE RING AND COVER, SEE DETAIL S10.
5. FOR MANHOLE STEPS SEE DETAIL S15. STEPS TO BE INSTALLED IN A VERTICAL ROW ON 16" CENTERS.
6. CHECK FOR BUOYANCY
7. ALL PIPE PENETRATIONS SHALL HAVE A BOOT CONNECTION IN ACCORDANCE WITH DETAIL S12

STANDARD PRECAST CONCRETE MANHOLE

STANDARD
CONSTRUCTION
DETAILS



CITY OF
savannah
WATER RESOURCES AND PUBLIC WORKS BUREAU
Planning & Engineering

SCALE: N.T.S.

DATED: SEP 2013

PLATE NUMBER:

S1